

Amendments To The Claims:

Please amend the claims as shown.

1– 11. (canceled)

12. (currently amended) A method for updating communication services in a communication network comprising:

~~providing~~~~containing~~ multiple communication components, including a plurality of components having different hardware and software functionalities for performing different functions, wherein some of the components ~~which use or and provide the same communication services in the network;~~~~comprising~~:

providing to a plurality of the components an identical software-controlled communication service that provides a feature to facilitate communication between at least two ~~with a plurality of the components;~~

identifying at least some of the components providing the identical software-controlled communication service in the communication network;

initiating a comparison of information by one of the components to compare release information of software controlling the communication service on each of the identified components when providing the identical software-controlled service; and

initiating a software update for one component when a comparison identifies that the release on said one component is different from the release on a second ~~another~~ of the components, wherein software with a more up-to-date release is sent from a third communication component to a said one component with an earlier release.

13 - 14. (canceled)

15. (previously presented) The method of Claim 12, wherein comparison of release information is repeated at settable time intervals.

16. (previously presented) The method Claim 12, wherein the network includes a packet-switching network.

17. (previously presented) The method of Claim 12, wherein the identical software-controlled service is selected from the group consisting of gateway functionality, voicemail server service, and address server service.

18. (currently amended) A method for providing communication services in a communication network, comprising:

providing communication services in ~~at~~the communication network formed of components having different hardware and software functionalities for performing different functions, with each of multiple ones of the communication components, ~~some of the~~ components capable of providing an identical software-controlled service;

enabling the identical software-controlled service in a first of the communication components; and

activating, or updating software pertaining to, the identical service in a second of the communication components by downloading software pertaining to the identical service ~~from the first communication component to the second communication component, wherein,~~ ~~wherein software pertaining to the service is sent from a third communication component to the~~ second component.

19 - 22. (canceled)

23. (previously presented) The method as claimed in Claim 18, wherein the first communication component initiates updates of software in the second component and in multiple other communication components.

24. (previously presented) The method as claimed in Claim 18, wherein the first communication component in the communication network has been provided with a most up-to-date release for operation thereon and for downloading to other components.

25. (currently amended) A method for updating a service in a packet-switching communication network, comprising:

providing a communication network formed of components having different hardware and software functionalities and performing a plurality of communication services with the components, including providing an identical software-controlled service on a first servent communication component and a second servent communication component, the components communicating peer-to-peer;

initiating a comparison by the first of the components to compare release information of the software controlling the service on at least the second component relative to software controlling the service on at least the first component; and if the releases are different,

identifying a more up-to-date release installed on one of the a third servent  
communication components; and

initiating a software update by downloading the more up-to-date release from said third  
one of the components to one of the another components for which release information has been  
compared, ~~wherein wherein the step of initiating a software update by downloading the more~~  
~~up-to-date release from said one of the components to another component for which release~~  
~~information has been compared is effected by downloading software from a third servent~~  
~~communication component.~~

26 -28. (canceled)

29. (previously presented) The method as claimed in Claim 25, wherein the comparison of the release information is repeated at settable time intervals.